Three-Lobed Torque Handles 24711.0507



Product Description

Torque handles are used wherever a limitation of the exerted hand force is required. The three-lobed torque handle with integrated torque mechanism allows a defined torque limit during tightening. Reaching the torque results in an "over-locking". For releasing the torque is transmitted indefinitely.

These handles combine the functionality of a ratchet wrench with the modern and ergonomic design of a three-lobed handle.

Material

Сар

Plastic, light grey

Torque mechanism

Steel, hardened

Handle

• Thermoplastic PA-HP, glass fibre reinforced, black, matt

Inner part

Steel, blackened

Screw


· Steel, blackened


More information

Further products


• Torque Handles

Drawing





picture 1



Order information

Dimensions							Tightening torque	Ĩ	Art. No.
d ₁	d ₃	I	d4	d₅	h ₁	h ₂	+/- 10% max.		
[mm]							[Nm]	[9]	
with screw – picture 2									
80	M10	40	19	34.1	56.2	16.8	5.5	203	24711.0507

Application example



Compliance

RoHS compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c.

Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 27.06.2024.

Contains Proposition 65 substances

Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Free from Conflict Minerals

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.