# Flat Knurled Nuts • DIN 467 EH 24760.



### **Product Description**

Knurled nuts are very versatile. Three material versions for the different requirements

- Steel, blackened •
- Steel, zinc-plated by galvanization
- Stainless steel
- are available.

Knurled nuts can be easily tightened and released by hand. The ribbed outer surface of the nut prevents slipping when tightening / releasing with the fingers. The flat knurled nuts are manufactured according to DIN 467.

#### **Material**

- Steel, blackened, quality 5Steel, zinc-plated by galvanization, quality 5
- Stainless steel 1.4305, dull blasted

#### More information


#### Notes

Knurling pitch and knurling depth may differ from DIN.

#### **Further products**

• High Knurled Nuts, DIN 466

#### Drawing



### **Order information**


		Art. No.				
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	h	k	-	
		[mm]				
Steel, blackened						
М 3	12	6	3	2.5	2.1	24760.0030
М 4	16	8	4	3.5	5.1	24760.0040
M 5	20	10	5	4.0	9.4	24760.0050
M 6	24	12	6	5.0	17.0	24760.0060
M 8	30	16	8	6.0	32.0	24760.0080
M10	36	20	10	8.0	61.0	24760.0100
M12	40	22	12	10.0	92.0	24760.0120
Steel, zinc-plated by gal	vanization					
М 3	12	6	3	2.5	2.0	24760.0430
M 4	16	8	4	3.5	5.0	24760.0440
M 5	20	10	5	4.0	9.0	24760.0450
M 6	24	12	6	5.0	17.0	24760.0460
M 8	30	16	8	6.0	32.0	24760.0480
M10	36	20	10	8.0	62.0	24760.0500
M12	40	22	12	10.0	92.0	24760.0512 <sup>1</sup>

<sup>1)</sup> DIN standards do not include these dimensions.

	<b></b>	Art. No.				
d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	h	k	-	
		[g]				
Stainless steel 1.4305						
М 3	12	6	3	2.5	2.1	24760.0230
M 4	16	8	4	3.5	5.1	24760.0240
M 5	20	10	5	4.0	9.4	24760.0250
M 6	24	12	6	5.0	17.0	24760.0260
M 8	30	16	8	6.0	32.0	24760.0280
M10	36	20	10	8.0	61.0	24760.0300

<sup>1)</sup> DIN standards do not include these dimensions.

## Application example



## Compliance

For detailed compliance information please select the desired article number.